



## QuickSeam Flashing

**Firestone Item Number:**

**W56RAC1605**

**W56RAC1615**

**DESCRIPTION:**

QuickSeam Flashing is a semi-cured EPDM flashing laminated to cured seam tape. QuickSeam Flashing is used to flash gravel stops and other details as specified in the Firestone Specifications and Details.

**METHOD OF APPLICATION:**

Use QuickPrime Plus and QuickScrubber or QuickScrubber Plus pad and handle to clean and prime membrane and metal mating surfaces. Refer to Firestone Installation Instruction Sheet for QuickSeam Flashing.

**PHYSICAL CHARACTERISTICS:**

1. Excellent moisture resistance.
2. Excellent resistance to heat and cold.
3. Excellent green tack.
4. QuickSeam Flashing is semi-cured. **Do not stretch.**

**STORAGE:**

1. Store in original unopened containers at temperatures between 60° F (15.6° C) and 80° F (26.7° C).
2. Do not store in direct sunlight or at temperatures above 80° F (26.7° C).
3. When exposed to lower temperatures, restore to room temperature prior to use.

**PACKAGING:**

1. 100' (30.5 m) rolls, 2 rolls per carton.
2. 36 cartons per pallet.
3. Rolls may consist of two separate sections of QuickSeam Flashing to make 100' (30.5 m) total length.

**Note: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.**

This sheet is meant only to highlight Firestone's products and specifications. Information is subject to change without notice. Firestone takes responsibility for furnishing quality materials, which meet Firestone's published product specification. As neither Firestone itself nor its representatives practice architecture, Firestone offers no opinion on, and expressly disclaims any responsibility for the soundness of any structure on which its products may be applied. If questions arise as to the soundness of a structure, or its ability to support a planned installation properly, the Owner should obtain opinions of competent structural engineers before proceeding. Firestone accepts no liability for any structural failure or for resultant damages, and no Firestone Representative is authorized to vary this disclaimer.

### PRODUCT DATA

**QUICKSEAM TAPE**

<u>Property</u>	<u>Minimum Performance</u>
Base:	Rubber Polymer
Color:	Black
Solvents:	None
Percent Solids:	100%
Cured State:	Cured
Thickness:	.045" (1.14 mm) ±.005" (.13 mm)
Width:	5-1/4" (133.3 mm) +0" (+0 mm), -1/16" (-1.6 mm)
Length:	100 lf (30.5 m)

**EPDM FLASHING**

<u>Property</u>	<u>Minimum Performance</u>
Base:	EPDM
Color:	Black
Solvents:	None
Percent Solids:	100%
Cured State:	Semi-cured
Thickness:	.045" (1.1 mm) ± 10%
Width:	5" (127 mm) +0" (+0 mm), -1/8" (-3.18 mm)
Length:	100 lf (30.5 m)

**SHELF LIFE:**

1. Shelf life of 6-9 months can be expected when stored at 60° F (15.6° C) and 80° F (26.7° C) in original unopened containers indoors.
2. Shelf life will be shortened if exposed to elevated temperatures.

**PRECAUTIONARY DATA:**

1. Refer to Material Safety Data Sheets (MSDS).

**LEED INFORMATION:**

Post Consumer Recycled Content:	0%
Post Industrial Recycled Content:	0%
Manufacturing Location:	Prescott, AR Michigan Center, MI



Flashing Material for Roofing Systems  
As to an External Fire Exposure Only  
61P2  
See UL Directory of Products  
Certified for Canada  
And UL Roofing Materials  
And Systems Directory  
R9516

**Firestone Building Products Company**

A Division of BFS Diversified Products, LLC  
310 E. 96<sup>th</sup> Street, Indianapolis, IN 46240  
Sales: (800) 428-4442 • Technical (800) 428-4511  
www.firestonebpcco.com